

NEMA TYPE 12 P.S. 12GA ENCLOSURE WITH CONTINUOUS HINGES 3 POINT LATCH, PADLOCKABLE (TYPICAL) ACTUAL LAYOUT MAY VARY WITH HORSEPOWER DIMENSIONS: 60" H X 72" W X 14" D 12 INCH LEGS

TYPICAL CONTROL PANEL LAYOUT SCALE: NTS

LEGEND:

- F: INTRINSICALLY SAFE CIRCUITS AND WIRING
 C: INTRINSICALLY SAFE FIELD WIRING TERMINALS
- A: NON-INTRINSICALLY SAFE CIRCUITS AND WIRING E: NON-INTRINSICALLY SAFE FIELD WIRING TERMINALS
- M1: INTERNAL MARKING (SEE NOTE 7-B) M2: INTERNAL MARKING (SEE NOTE 7-A)

NOTES:

- 1. SPACINGS (6.1)
- 1/4 INCH SPACING BETWEEN THE TERMINALS FOR CONNECTION OF FIELD WIRING OF DIFFERENT INTRINSICALLY SAFE CIRCUITS AS DEFINED BY THE BARRIER CONTROL DRAWING.
- A. CIRCUITS FROM TWO DIFFERENT BARRIERS. B. TWO CIRCUITS FROM THE SAME BARRIER.
- 2. SEPARATION OF CIRCUITS (7.1-7.3) 5 INCHES BETWEEN INTRINSICALLY SAFE FIELD WIRING TERMINALS AND NON-INTRINSICALLY SAFE CIRCUITS (C AND A)
- 3. SEPARATION OF CIRCUITS (7.1-7.3) 5 INCHES BETWEEN NON-INTRINSICALLY SAFE FIELD WIRING TERMINALS AND INTRINSICALLY SAFE CIRCUITS AND WIRING (E AND F)
- 4. SEPARATION OF CIRCUITS (7.1-7.3)
- 5 INCHES BETWEEN INTRINSICALLY SAFE INTERNAL WIRING AND NON-INTRINSICALLY SAFE CIRCUITS AND WIRING (A TO F)
- 5. SEPARATION OF CIRCUITS (7.1-7.3)
- 8 INCHES FROM INTRINSICALLY SAFE FIELD WIRING TERMINALS AND NON-INTRINSICALLY SAFE FIELD WIRING TERMINALS (C TO E)
- 6. GROUND TERMINAL (8.1) GND TERMINAL DEDICATED TO THE INTRINSICALLY SAFE BARRIER SHALL BE BOUNDED TO THE EQUIPMENT GROUNDING SYSTEM
- 7. MARKING (10.1-10.2)
- INTERNAL MARKING:
- A. "INTRINSICALLY SAFE FIELD WIRING TERMINALS" (F) "WARNING: SUBSTITUTION OF COMPONENTS MAY IMPAIR INTRINSIC SAFETY"
- (E) MUST BE IN THE INTRINSICALLY SAFE AREA OF THE PANEL
- 8. MARKING (10.1-10.2) EXTERNAL PANEL MARKING:

REVISIONS

DATE BY DESCRIPTION 3/14/11

HE (A) MENT RE DEP.



SHEET 4 OF 4